



BP-T3BH

BP-T3BH

80mm thermal receipt printer

Affordable and Powerful

Wholly immerse in receipt printing with 3-in-1 interface devices



1. 3-in-1 interface with cables of RS232 and USB as bundled

BP-T3 is an absolute good for your receipt printing with 260mm/second print speed. It is built with LAN + USB HID + RS232 (3-in-1 interface) and included with RS232 + USB cables. It meets nearly most application working environments with no interface change needed. It is simple and easy.

2. Supports Multiple interface languages

BP-T3 supports international languages changes by the utility selected. Furthermore, it supports Chinese languages changed between Traditional and Simplified Chinese ones on the same motherboard.

3. QR Code (2D) supported

Besides the general and popular 1D barcode symbologies printings supported on BP-T3, BP-T3 already built-in QR code printing function, which is the popular applications in the market.

4. Powerful drivers and OPOS

BP-T3 is with the powerful drivers to support your working OS environments (Windows 9X/ME/2000/XP/NT/Vista, Windows 7/8 and Linux).

Graphic printing speed can be increased from 27mm/second to 100mm/second by driver mode print speed with DIP SWITCH set (SW-8)

OPOS driver is available.

5. NV Flash Buffer

BP-T3 built-in 256K bytes NV Flash buffer to support logo downloading on your receipt printing, and it is helpful to your receipt printing with more attractive images.

Ordering Information:

BP-T3BH: 80mm thermal receipt printer, w/Auto Cutter, 260mm print speed, RS232 +USB HID +LAN interface, Black, w/USB and RS232 cable as standard



Technical Specifications

Model Numbers		BP-T3BH		Interface		Dsub 9 pin female connector, default with 9600 or up to 115200 bps baud-rate (straight)
Printer	Printing Method	Direct Thermal		Serial		
	Printing Direction	Line printing		USB	USB 2.0 full-speed (HID signal)	
Mechanism	Max Print Width	79.5mm ±0.5mm		Ethernet	10/100Base-T	
	Effective Print Width	72mm		Cash Drawer	DC 24V, 1A, RJ-11 socket	
	Character Size	Font A: 12 x 24 dots ; Font B: 9 x 17 dots		Print commands	ESC/POS OPOS driver available	
	Character per line	Font A: 48 ; Font B: 64		Input Buffer	256KB for NV Flash buffer 1024KB for Data receive buffer	
Printer Head	Printing Speed	260mm/sec		Paper	Paper Width	79.5mm ±0.5mm
	Printer Density	576 dots/line, 203dpi			Roll diameter	Max. 83mm
Print font	Life	100 KM		Thickness	0.06~0.08mm	
	ASCII code	13 international character set		Environment		
	Chinese	Big 5 / GB123		Operating	0°C ~ 45°C; 20%RH ~ 85%RH	
Bar code	1D: UPC-A/ UPC-E/ JAN13(EAN13)/ JAN8(EAN8)/ CODE39/ Interleaved 2 of 5/ CODABAR/ CODE93/ CODE128			Storage	-20°C ~ 60°C; 5%RH ~ 95%RH	
		2D: QR CODE			Power supply	
	Cutter	Auto Cutter	Full cut or Partial cut		Input	100V AC – 220V AC, 50-60Hz (≤1.5A)
Driver	Life Span	1,000,000 times		Output	DC +24V / 2.5A	
		Win9X/WinME/Win2000/WinNT/WinXP, Win Vista, Win7/WIN 8/Linux		Dimension	185(L) x 140(W) x 134mm (H)	
				Weight	1.5Kgs (without cable)	
				Black Mark	Supported	
				Beep Tone	Standard for Head Open, Paper End. Driver setting for After Printing.	



Birch is a trademark of Birch Technology U.S.A. Inc
All other products, brands or companies are trademarks or registered trademarks of their respective companies.

Specifications are subject to change without prior notice

Contact us for details